Technische datasheet Ecoline Impact



Productfoto's:	
Product description:	Rubber floor mat, developed for fitness use. Product contains SBR granulate (made from recycled European car tyres), bonded through warmth with high quality PU- binder. Upper side flat with a profiled base. Protect strength equipment from damage, thermally insulate the floor, cushion falls through the use of a unique "wave" structure. The optimal working temperature of the article is from -40°C to +40°C. The mats are non-slip, resistant to noise and vibration, absorb shock and are ideal for exercise areas with weights and heavy equipment.
Dimensions:	1000x1000x20mm.
Size tolerance thickness:	+/- 8%
Size tolerance length-width:	+/- 1 %
Weight m ² :	17kg. (+/- 200gr).
Weight tolerance:	- 5% / +8% (5+3 because of the use of pigments)
Behaviour to fire:	EFL-S1 NORMA PN-EN ISO 9239-1:2010; PN-EN ISO 11925-2:210
Abrasiveness:	Abrasiveness at a force of 50N (2000 cycles) - weight loss ~ 2,5%
Anti-slip properties:	Determination of the value according to DIN 51 131 standards dry and wet surface. Result: dry: 56, wet: 43
Environmentally:	Environmentally friendly, REACH compliant



Handelsweg 3 1751 HE Schagerbrug 0224571468 bosrubber.nl

Bel voor meer informatie (+31) 224-571468 of mail naar info@bosrubber.nl voor meer informatie

